Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

Projector XP80

Compact projector for business presentation

Issue November 2007

Pages 2

With outstanding performance and compact dimensions the Projector XP80 from Fujitsu Siemens Computers will brighten up any presentation.

The Projector XP80 offers high resolution and contrast, excellent brightness and very low weight. This makes the Projector XP80 the ideal choice for busy travelling users or business executives, even for presentations in fully lit rooms.

Reliability

- High quality and stability
- Reliability of delivery
- Single Chip DLP™ XGA-technology

Ergonomics

- Digital Keystone correction
- High contrast and excellent focus
- 1700 lumens for best visual experience

Usability

- Very low weight 1.1 kg
- Integrated loudspeaker
- Easily user replaceable lamp
- Ease-of-use multi-language OSD menu
- Plug & Play
- Digital and analogue PC, Composite, S-Video and Audio connectivity
- HDTV compliant

Technology	Single Chip DLP™ XGA
Contrast typical	2000 :1
Brightness typ	1700 lm
Colors	16.7 Million/24bit

Optics

Lens	1.16:1 manual
Diagonal image size	0.8 – 5.3 m
Throw distance	1.5 – 10 m
Keystone correction	+/- 5 degrees digital
Uniformity	70%

Frequencies

Horizontal	15 - 90 kHz
Vertical	50 - 85 Hz
Bandwidth	112 MHz

Supported Graphic Modes/Formats

Pixels	1280 x 1024
Pixels	1152 x 864
Pixels	1024 x 768 (native)
Pixels	1400 x 1050
Pixels	1280 x 800
Pixels	140 x 900
Pixels	832 x 624 (MAC)
Pixels	800 x 600
Pixels	640 x 480

Video Input Compatibility/Modes

NTSC, PAL, Secam, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)

Input Sources

Computer	DVI-I (with HDCP support)
Video	S-Video, Composite, 3.5 mm jack
Audio	2.6 mm mini jack

Control	USB for service only
OSD languages	English, French, Spanish, German, Italian, Japanese, Korean, Swedish, Chinese, Russian, Portuguese

Electrical values

Rated voltage	100-240 V, +/- 10%
Frequency	50-60 Hz
Power draw	
Operating (normal/eco)	< 195 W/ 165 W
Standby mode	< 8 W
Protection class	1

Temperatures / dimensions / weight

Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	5°C to 35°C
Dimensions	
(H x W x D)	73.5x192.3x164.5 mm
Weight	1.1 kg
Operating noise typical	38 db(A**)**
Reliability typical	
Lifetime of Lamp normal(eco)	5000h (4000h)

Compliance with standards

Product safety	UL 1950 CSA 22.2 No.950 FCC Class A
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024, EN61000-3-2/-3);

Supplied material

Cables / adapter	DVI-I to VGA 3 pole Power Cable, 1.8 m Audio cable (mini jack), 1,8 m Composite Video Cable,1,8 m
Accessories	Soft carrying case Remote control Lens cap User guide on CD
Warranty	Projector XP80: 2 years Lamp: 90 days or max. 500 hours
Special features	Kensington Lock prepared User replaceable lamp
Order Code	S26361-K1215-L100
EAN Code	4 333 64 30 90 678

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu-siemens.com/terms_of_use.html

Copyright © Fujitsu Siemens Computers 11/2007

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp